

Ramos Fleet Oil PCMO 10/30 and 5/30

Product Description:

Ramos Fleet Oil is a premium multi-grade motor oil formulated to provide excellent all weather engine protection for gasoline powered cars and light trucks. Ramos Fleet PCMO contains sheer stabilizers, viscosity index improvers to provide easier cold weather starting and better high temperature protection demanded by modern high output engines. This oil meets API Classification SL and can be used in place of SJ,SH, and SG rated oils. The oils are formulated with high viscosity index, thermally stable base stock and selected additive systems to provide protection for the demands put on modern crankcase lubricants. These oils provide a high level of protection against wear, rust and corrosion, piston scuffing and combustion chamber deposits, high temperature oxidization and valve train wear.

Application:

- Gasoline powered light trucks and passenger cars.
- Equipment powered by small gasoline engines.

Features:

- Has excellent wear protection that promotes engine durability
- Outstanding oxidation resistance to help maximize service life
- Meets API Classification SL ,SJ Energy Conserving and meets ILSAC GF-3 Specifications
- Meets Car Manufactures Warranty Requirements for Gasoline Engines where API SL oils are specified.

Typical Properties of Ramos Fleet Oil 30

	5/30	10/30
Product Code	BR1963	BR1961
Gravity, API	32.60	31.37
Viscosity		
@ 40 C cSt	66.16	69.04
@ 100 C cSt	10.75	10.5
@ 100 F, SUS	337	354
@210 F, SUS	63	62
Viscosity Index	153	138
Flash Point, (Fahrenheit)	420	430
Pour Point, (Fahrenheit)	-33	-17