

Ramos Fleet Hydraulic Oil ISO 32, 46, 38

Product Description:

Ramos AW Hydraulic is a premium quality anti-wear hydraulic fluids designed for use in all types of high pressure, high speed hydraulic pumps used in industrial, mobile, and marine hydraulic systems. This product is well suited for highly accurate machine tool and industrial robot hydraulic systems.

Typical Application:

- Hydraulic including gear, vane, and piston pump
- Circulating oil systems
- General machine lubrication

Outstanding Features:

- Outstanding wear protection for critical system components
- Excellent rust and corrosion protection
- Good foam resistance

Description:

Ramos Hydraulic Oil is a low zinc level anti-wear hydraulic fluid formulated with high quality paraffinic base oils and selected additives that provide excellent wear protection plus oxidation resistance, rust and corrosion protection, and foam resistance. It also has excellent low temperature properties for cold start-ups

Typical Inspection tests:

Grade, ISO:	32	46	68
Product Code:	BR1955	BR1956	BR1957
Flash Point, COC, Degrees F	415	425	445
Pour Point, COC, Degrees F	-35	-25	-25
Viscosity			
cSt @ 40 C	32.7	46.3	68.1
cSt @ 100 C	5.4	6.7	8.6
SUS @ 100 F	169	239	353
SUS @ 210 F	44.4	48.7	55.2
Viscosity Index	98	96	97